



# A SUB-SPACE METHOD TO DETECT MULTIPLE WIRELESS MICROPHONE SIGNALS IN TV BAND WHITE SPACE

**Dinesh Datla, Harpreet Dhillon, Jeong-O Jeong, Mike Benonis, Michael Buehrer and Jeffrey Reed**

1

**Presenter: Jeong-O Jeong**

**Wireless @ Virginia Tech, Blacksburg VA, USA**


**Email: {ddatla, harpreet.dhillon, jeongo9, mjb8h, buehrer, reedjh} @ vt.edu**

# ORGANIZATION


- Introduction
- Noise Characterization
- Singular Value Decomposition
- SVD-Based WM Sensing Algorithm
- Empirical Results
- Conclusion and Future Direction
- Acknowledgement

# INTRODUCTION – WIRELESS MICROPHONE SIGNALS

- Analog wide-band FM: occupied bandwidth  $< 200\text{kHz}$
- RF power  $\sim 50\text{ mW}$
- Operate at frequency any multiple of  $25\text{ kHz}$  in the high-band VHF and UHF TV bands



PSD of typical wireless microphone signal




Wireless microphone signal in TV band with narrowband interference


# INTRODUCTION - SPECTRUM SENSING ALGORITHMS

- Energy Detection
- Matched Filtering
- Cyclostationarity-based
- Eigenvalue-based
- Covariance-based

# NOISE CHARACTERIZATION – STATISTICAL PROPERTIES




Histogram of background noise computed from measurement data.




Variance of background noise at different time instances.

- Truncated Gaussian histogram
- Stationarity - Variance does not vary significantly with time

# NOISE CHARACTERIZATION- AUTOCORRELATION




Autocorrelation of band-limited background noise samples.




Autocorrelation of loud(modulated) WM signal with colored noise.

# POWER SPECTRAL DENSITY



PSD of band-limited background noise.

- No wireless microphone signal present



PSD of modulated WM signal with colored noise.

- Wireless microphone signal at 10.625 MHz

# SINGULAR VALUE DECOMPOSITION


- SVD of a  $m \times n$  matrix  $\mathbf{M}$  gives the factorization

$$\mathbf{M} = \mathbf{U}\mathbf{S}\mathbf{V}^*$$

- $\mathbf{U}$  = an  $m \times m$  unitary matrix
  - $\mathbf{S}$  = an  $m \times n$  diagonal matrix with nonnegative real numbers on the diagonal
  - $\mathbf{V}^*$  = an  $n \times n$  unitary matrix
- Diagonal entries of  $\mathbf{S}$  are singular values of  $\mathbf{M}$




# SVD BASED WM SENSING ALGORITHM – TRAINING PHASE



$$\widehat{\mathbf{R}}_{\eta}$$



Average noise correlation matrix

# SVD BASED WM SENSING ALGORITHM – DETECTION PHASE



# EMPIRICAL RESULTS

- Multiple signals were detected
- Intermodulation components could not be distinguished from the wireless microphone signals



## CONCLUSION

- Wireless microphone signals at low SNR can be detected using our method
- More measurements have to be conducted under different wireless environments to obtain more accurate test statistics thresholds
- Analysis of the complexity and performance tradeoffs need to be performed

# ACKNOWLEDGEMENT

- Qualcomm Inc.
- Dr. Steve Shellhammer

The wireless microphone signals used in evaluating the spectrum sensing techniques described in this paper were provided by Qualcomm as part of the Qualcomm Cognitive Radio Contest. The contest was held between students from a number of universities in North America to find out which team had the best wireless microphone spectrum sensing technique

# REFERENCES

- [1] F. C. Commission, "Second report and order and memorandum opinion and order (fcc 08-260)." US Government Printing Office, Washington, November 4 2008.
- [2] D. Cabric, S. M. Mishra, and R. W. Brodersen, "Implementation issues in spectrum sensing for cognitive radios," in *Conference Record of the Thirty-Eighth Asilomar Conference on Signals, Systems and Computers*, vol. 1, pp. 772–776, 2004.
- [3] A. Mossa and V. Jeoti, "Cyclostationarity-based spectrum sensing for analog tv and wireless microphone signals," in *First International Conference on Computational Intelligence, Communication Systems and Networks CICSYN '09*, pp. 380–385, July 2009.
- [4] Y. Zeng and Y.-C. Liang, "Eigenvalue-based spectrum sensing algorithms for cognitive radio," *IEEE Transactions on Communications*, vol. 57, pp. 1784–1793, June 2009.
- [5] Y. Zeng and Y.-C. Liang, "Spectrum-Sensing Algorithms for Cognitive Radio Based on Statistical Covariances," *IEEE Transactions on Vehicular Technology*, vol. 58, pp. 1804–1815, May 2009.
- [6] S. M. Saberali and H. Amindavar, "Weak BPSK signal detection in the presence of cochannel interference with time varying characteristics using maximum entropy principle," in *IEEE International Conference on Acoustics, Speech and Signal Processing ICASSP 2008, (Las Vegas, NV, USA)*, pp. 3193 – 3196, March 31 - April 4 2008.
- [7] S. Xu, S. Xu, and H. Wang, "SVD based Sensing of a Wireless Microphone Signal in Cognitive Radio Networks," in *International Conference on Computational Science (ICCS), (Krakw, Poland), June 2008*.
- [8] Shellhammer, S.J.; Sadek, A.K.; Wenyi Zhang; , "Technical challenges for cognitive radio in the TV white space spectrum," *Information Theory and Applications Workshop, 2009* , vol., no., pp.323-333, 8-13 Feb. 2009

# QUESTIONS

