

Low-Complexity SDR Implementation of IEEE 802.15.4 (ZigBee) Baseband Transceiver on Application Specific Processor

Amanullah Ghazi, Jani Boutellier, Jari Hannuksela, Olli Silven, Janne Janhunen



Department of Computer
Science and Engineering
Tietotekniikan Osasto

UNIVERSITY of OULU
OULUN YLIOPISTO





Outline

- IEEE 802.15.4
- TTA Processor Architecture
- Transmitter and Receiver Design
- Performance Figures
- Conclusion



Department of Computer
Science and Engineering

Tietotekniikan Osasto

UNIVERSITY of OULU
OULUN YLIOPISTO






Goals

- Performance analysis of SDR realization on an Application Specific Processor
- Modifying existing receiver algorithms to suit SDR realization
- Designing Application Specific Processor for the implementation of algorithms






IEEE 802.15.4 Standard

- Low data rate Wireless Personal Area Network (LR-WPAN)
- IEEE provides physical and MAC Layer specifications
- Frequency: 2.4 GHz
- Bit rate: 250 kbps
- Modulation: O-QPSK with Half-sine pulse shape
- Coding: Direct Sequence Spread Spectrum based on 32-bit orthogonal PN sequences




Transport Trigger Architecture (TTA)



- Processor design paradigm where computations happen as side effect of data transport

Transmitter Design




- Frame Formatter: Packet as per the specification
- Chip Mapper: For Direct Sequence Spreading
- O-QPSK Modulator
- Half Sine Pulse Shaper



TTA Processor for Transmitter

- Resources on Processor
 - 2 ALUs
 - 1 LSU
 - 1 GCU
 - 1 FU for Multiplication
 - 4 register files with five 32-bit registers each
 - SFU for serial input and output of data
 - 6 data Buses
- Gate Count Estimate: 16k

Receiver Design




- Non-coherent Detection

- Based on Asynchronous Zero Crossing Detector (AZCD)
- MSK interpretation of O-QPSK with Half sine Pulse Shape
- Phase and timing synchronization not needed
- Easy to implement on low power and low cost devices

Rx Design...

- AZCD Detector



– Number of phase axes: 8

Rx Design...

- ZCD

- Phase Axis Generation: To work with lower modulation index

$$\begin{cases} i_k = i \cdot \cos \theta_k + q \cdot \sin \theta_k \\ q_k = -i \cdot \sin \theta_k + q \cdot \cos \theta_k \end{cases}$$

- Zero Crossing Detection: Detects the direction of phase axis crossing for a particular pair of axes

$$D_k = 1/2[i_k \cdot (q_k - q_{k-1}) - q_k \cdot (i_k - i_{k-1})]$$

- $D_k = -1$ (clockwise), 1 (Anti-clock), 0 (No crossing)
- Saturation

$$C_i = \text{sat}(C_{i-1} + D_k)$$

- Shape Device:
$$S_i = \begin{cases} S_{i-1} & \text{if } C_i = 0 \\ C_i & \text{otherwise} \end{cases}$$



Rx Design..

- Down Sample
 - AZCD algorithm provides shape of the MSK/O-QPSK Coded signal
 - E = Oversampling Factor, M = number of Phase axis
 - Down Sample by $E/2 * M/2$
- Preamble Detection
 - Correlate incoming signal with preamble chip to detect packet
 - Down sampling done at multiple offset for best preamble correlation (Best chip time)

Rx Design

$$\begin{aligned} a_k &= 0 - \text{QPSK} \\ d_k &= \text{MSK} \end{aligned}$$

- Correlator

- De-spreading of chip sequence
- Spreading codes encoded with MSK/O-QPSK coding equation

$$\begin{cases} d_{2k} = a_{2k+1}a_{2k} \\ d_{2k+1} = -a_{2k+2}a_{2k+1} \end{cases}$$

- Detected chips packed in 32-bit memory
- replace multiply-and-accumulate operation by bitwise XOR and count number of 1s in 32-bit register
- Least number of 1s => Best correlation






TTA Processor for Receiver

- Resources on Processor
 - 8 ALUs
 - 2 LSU
 - 1 GCU
 - 8 register files with eight 32-bit registers each
 - SFU for serial input and output of data
 - 8 SFU for computing sign of a number
 - 1 SFU for Saturation, 1 SFU for counting 1s
 - 16 data Buses
- Gate Count Estimate: 95k



SER Performance



Required Sensitivity = -
85 dBm
 $E_b/N_0 = 19$ dB
NF = 7 dB



Performance

- Cycle count for transmitter
 - $\text{CPU Cycle} = 1088 * \text{PPDU Size (Byte)} + 23$
 - Clock requirement for 250 kbps = 35 MHz
- Cycle count for receiver
 - 5930 CPU cycles/byte of data
 - Preamble Detection overhead: 32k cycles
 - Clock requirement: 200 MHz




Conclusion

- TTA processors could provide an ideal platform for SDR implementation of low power and low cost wireless standards.
- Data throughput of 250 kbps achieved.

Parameters	System-on-chip	SDR on GPP	SDR on ASP (TTA)
Programmability	No	Yes	Yes
Integration with Sensor Nodes	Yes	No	Yes
Real-time Processing	Yes	No	Yes
Low-Cost	Yes	NA	Yes

- The SER performance of the demodulator is in agreement with IEEE 802.15.4 requirements.
- The processor have low gate count estimates, allowing for a low power and low cost implementation.





Thank You!
Questions?



*Department of Computer
Science and Engineering*

Tietotekniikan Osasto

UNIVERSITY of OULU
OULUN YLIOPISTO

