

A Dynamic Spectrum Access on SDR for IEEE 802.15.4e networks

Rafik Zitouni, Laurent George[‡] and Yacine Abouda

LACSC laboratory-ECE Paris

[‡] UPEMLV, LIGM/ ESIEE Paris

zitouni@ece.fr, [‡]laurent.george@univ-mlv.fr and abouda@ece.fr

March 23, 2015





ECE
PARIS

UNIVERSITÉ
— PARIS-EST

Overview

- 1 Context and Related Works
 - IEEE 802.15.4e
 - Time Slotted Channel Hopping (TSCH)
 - SDR for IEEE 802.15.4
- 2 Implementation of Dynamic Spectrum Access
 - Experiments and results
- 3 Conclusion and perspectives


Context and Related Works



- Dynamic Spectrum Access (DSA) or spectrum sharing is real time adjustments of spectrum utilization. It is based on rewarded information of SS

IEEE 802.15.4e


- **IEEE 802.15.4¹** standard defines PHY and MAC layers for LR-WPAN
- 2450 MHz O-QPSK (ISM)
- 868/915 MHz BPSK (ISM)
- 950 MHz GFSK
- .etc



¹ working groups, I. S. (2012). *Part 15.4: Low-Rate Wireless Personal Area Networks (LR-WPANs)*. IEEE Computer Society


Time Slotted Channel Hopping (TSCH)

- The main new contribution of **IEEE 802.15.4e** is Time Slotted Channel Hopping (TSCH) access mode
 - Allowing distributed implementation with TimeSlotted (One timeslot can be used by multiple links at the same time)
 - Channel Hopping, to give resilience to interference/multi-path fading



Time Slotted Channel Hopping (TSCH)

- Example of Link = (Timeslot , Channel Offset)²



- The two links from **B** to **A** are dedicated
- **D** and **C** share a link for transmitting to **A**
- The shared link does not collide with the dedicated links

²working groups, I. S. (2012). *Part 15.4:Low-Rate Wireless Personal Area Networks (LR-WPANs)*.

Time Slotted Channel Hopping (TSCH)

- Central frequency of each channel is statically defined
- TSCH is proposed only for 2450 MHz band channels
- The channel allocation depends only on the time slots and not on the link quality
 - Link Quality Indicator (LQI) (values from 1 to 255) indicates the energy strength and quality of received data
- TSCH needs a timeslot synchronization and extra acknowledgements transmissions
- Changing dynamically channels in TSCH is not expected without MAC protocol coordination.

Time Slotted Channel Hopping (TSCH)

- In addition Frequency Scarcity



Dynamic Spectrum Access

IEEE 802.15.4e

- Multiple PHY layers with specific frequency bands

PHY (MHz)	Frequency Band (MHz)	Propagation parameters		Parameters of data transmission		
		Chips rate (k chips/s)	Modulation	Bits rate (kb/s)	Symbols rate (k symbols/s)	Symbols
780	779-787	1000	O-QPSK	250	62.5	16-ary orthogonal
		1000	MPSK	250	62.5	16-ary orthogonal
868/915	868-868.6	300	DSSS + BPSK	20	20	Binary
		400	DSSS + O-QPSK	100	25	16-ary orthogonal
		400	PSSS + BPSK et ASK	250	12.5	20 bits PSSS
	902-928	600	BPSK	40	40	Binary
		1000	DSSS + O-QPSK	250	62.5	16-ary orthogonal
		1600	PSSS + BPSK et ASK	250	50	5 bits PSSS
950	950-956	—	GFSK	100	100	Binary
		300	BPSK	100	100	Binary
2450 (DSSS)	2400-2483.5	2000	O-QPSK	250	62.5	16 ary-orthogonal
UWB sub gigahertz	250-750					
2450 (CSS)	2400-2483.5	—	CSS + DQPSK	250	62.5	8-ary
				1M	166.667	16-ary bi-orthogonal
UWB low-high band	(3244-4742) (5944-10234)	Depends on environment conditions				

SDR for IEEE 802.15.4

- GNU Radio and USRP SDR platform
 - ① GNU Radio transceiver for 2450 MHz O-QPSK ³
 - ② GNU Radio transceiver for 868/915 MHz BPSK ⁴
 - ③ Energy detection based Spectrum Sensing ⁵
- Proposals:
 - Multi bands and multi specifications SDR
 - DSA throughout two frequency bands
 - Message-based algorithms for dynamic frequency selection

³Schmid, T. (2006). *Gnu radio 802.15. 4 en-and decoding*.
Networked & Embedded Systems Laboratory, UCLA, ...

⁴Zitouni, R., Ataman, S., George, L., and Mathian, M. (2012). *IEEE 802.15.4 transceiver for the 868/915 MHz band using Software Defined Radio*.
SDR Forum

⁵T. OShea, T. Clancy, H. E. (2007). *Practical Signal Detection and Classification in GNUradio*.
SDR Forum

Implementation of Dynamic Spectrum Access

Existing DSA techniques are :

- ① Dynamic Exclusive Use Model
- ② **Open Sharing Model**
 - Two frequency bands of IEEE 802.15.4 network is within unlicensed ISM spectral bands
 - IEEE 802.15.4e network can be considered as Secondary User (SU) of frequency bands whereas all unlicensed networks are Primary Users (PUs)
- ③ Hierarchical Access

Implementation of Dynamic Spectrum Access


Spectrum Sensing techniques are :

- ① **Energy-detector based sensing**
 - Simple to implement on GNU Radio
 - It is based on averaged Power Spectral Density (PSD)
- ② Cyclostationarity-Based Sensing
- ③ Matched-Filtering


Implementation of Dynamic Spectrum Access

- Software Defined Radio Settings

- Software chain of SU receiver (Rx)




- Software chain of SU transmitter (Tx)




Implementation of Dynamic Spectrum Access

- Software Defined Radio Settings

- 3 PU transmitter (Tx)



- Energy-sensor based spectrum sensing



$$E = \frac{1}{2N} \left[\sum_{n=-N}^N |s(n)|^2 \right] \quad (1)$$

where N is the number of samples and $s(n)$ is the sample number n

Implementation of Dynamic Spectrum Access

- Dynamic frequency selection

```
1: initialization();  
2: while energy > threshold do  
3:   spectrum_sensing(ss rx)  
4: end while  
5: while not receive_freq_ack(gmsk_rx) do  
6:   send_new_freq(gmsk_tx);  
7: end while  
8: while time ≤ timeout do  
9:   send_clear-to-receive(gmsk_tx);  
10: end while  
11: start_rx_802.15.4(802_15_4_rx);
```

Algorithm 1: Receiver (Rx)

Implementation of Dynamic Spectrum Access

- Dynamic frequency selection

```
1: initialization();  
2: while not new_freq_received do  
3:   receive_new_frequency(gmsk_rx);  
4: end while  
5: while not clear-to-receive(gmsk_rx) and (time  $\leq$  timeout) do  
6:   send_freq_ack(gmsk_tx);  
7: end while  
8: if clear-to-receive(gmsk_rx) then  
9:   start_tx_802.15.4(802_15_4_tx);  
10: else  
11:   receiver failed to receive clear-to-receive;  
12: end if
```

Algorithm 2: Transmitter(Tx)

Experiments and results

- Three USRP 1 devices, two devices represent SU transmitter (Tx) and receiver (Rx), whereas PU transmitter is the third one
- SBX daughter boards cover two frequency bands 2450 MHz and 868/915 MHz
- For each frequency, the energy sensed is the average of the magnitudes of each bin over 512 samples
- Parameters of energy sensor

USRP sample rate	channel bandwidth	chunk of bandwidth	number of bins	FFT window
4 MS/s	6250 Hz	3 MHz	480	640



$$\text{fft_size} = \left\lceil \frac{\text{usrp_rate}}{\text{channel_bandwidth}} \right\rceil$$

$$\text{bin_start} = \left\lceil \frac{\text{fft_size}}{8} \right\rceil$$

$$\text{bin_stop} = \text{fft_size} - \text{bin_start}$$



Experiments and results

- Spectrum sensor in an indoor environment



Experiments and results

• Packet Success Rate (PSR) and Packet Received Rate (PRR)



DSA improves **PSR by 80%** rather than the static frequency selection

Conclusion

- The IEEE 802.15.4 communications chains for 868/915 MHz and 2450 MHz have been combined to obtain DSA scheme
 - The DSA mechanism has been implemented on GNU Radio and USRP SDR platform
 - Communication chains of BPSK, OQPSK, GMSK and energy-sensor receiver have been assembled in one SDR
 - Energy sensor based Spectrum sensing has been carried out with real-world frequency hopping
 - Packet Success Rate (PSR) has been improved by 80 % via DSA mechanism compared to that obtained without DSA

Perspectives

- Define other parameters for frequency band hopping such as criticality levels and reliability of packets' transmission
- Improve the efficiency of our DSA mechanism using machine learning algorithms