

Dual Feed Omni-directional Antenna for Adaptive Polarization and MIMO Transceivers

Dr. Steven Schennum, Brian Gravelle, Caitlin Croskrey,
James Smock (Gonzaga University, Spokane, WA USA),
Robert Conley (Eigen Wireless, Liberty Lake, WA USA)




Motivation

- Adaptive Polarization (AP) can:
 - Reduce Polarization Dependent Loss (PDL)
 - Null Dominant Interferers
 - Improve MIMO system capacity
- Current Multi-Feed Multi-Polarized arrays are typically directional
- Arrays with deep pattern nulls cannot achieve the maximum AP improvements
- Goal: Develop low-cost omni-directional AP antenna for both MIMO and SISO systems

Polarization Review



- Signal of Interest at 45°
- Strong Vertical Interferer
- Optimal SINR is achieved at a polarization along the arc from 45° to horizontal



Gonzaga Design (OMPHA)

- Omni-directional Multiple Polarization Helical Antenna
- Two-element helical antenna
- Cross-polarized elements allow any polarization to be created
- 3D model captured and simulated with full wave electromagnetic solver
- Prototypes were produced and tested at Gonzaga's Smart Antenna and Radio Lab


Omni-directional Circular Polarization Helical Antenna



Helical Antenna Feed




Coaxial Feed Port

Antenna Feed




Simulated Element Results

- Single element results
 - 1.5 dBi gain at horizon
 - Azimuthal gain ripple less than 3dB
 - Cross polarization rejection 10 to 12dB
 - Axial ratio <2dB in 360°
 - Center frequency at 902
 - Return loss -8.75dB





Simulated Array Design

- Array of two orthogonal elements
 - RH & LH circular polarization
- Array combination less than $\frac{1}{2}$ wavelength
 - Supports co-linear arrays for increased gain
- Simulation Software
 - Ansys High Frequency Structure Simulator (HFSS)




Simulated Array Results

- Horizontal polarization resulting from equal phase & amplitude excitation





Horizontal




Vertical cross-pol

Simulated Array Results

- Vertical polarization resulting from 180° phase & equal amplitude excitation




Horizontal cross-pol



Vertical


Prototypes

- Individual RH & LH elements
 - On 3D printed forms
- Arrayed for Adaptive Polarization
- Tested in Anechoic chamber




Measured Single Helix

S11 from 820 to 1020 MHz




Measured Single Helix

- Azimuthal cut for LHCP Gain
- 2dB per div
- Plot maximum set at 2dBi




Measured Double Helix

S11 from 820 to 1020 MHz




Measured Double Helix

S11 from 820 to 1020 MHz




Measured Double Helix

- Azimuthal cut for Horizontal Gain
- 2dB per div
- Plot maximum set at 2dBi



AP Results for Smart Grid

Packet Error Rate: Fading & Polarization Scattering **Plus Interference**



Conclusion

- Benefits of this antenna:
 - Easily arrayed
 - Excellent azimuthal performance
 - Physical apertures much less than $\frac{1}{2}$ wavelength
 - Enables adaptive polarization systems
- Future efforts will:
 - Improve simulation accuracy to more closely match prototypes
 - Reduce size through dielectric loading
 - Construct co-linear and beamforming arrays
 - Improve measurement performance
 - Improve bandwidth



Thank You!

Questions?

Antenna Demonstration At Gonzaga Booth

Dr. Steven Schennum

schennum@gonzaga.edu

Brian Gravelle

bgravelle@zagmail.gonzaga.edu

Caitlin Croskrey

ccroskey@zagmail.gonzaga.edu

James Smock

jsmock@zagmail.gonzaga.edu

Robert Conley

bconley@eigenwireless.com

