

An Evaluation of Adaptive Equalizers on Non-Linear HF/Ionospheric Channel Models

Noel Teku*, Garrett Vanhoy*, and Tamal Bose*

***University of Arizona, Electrical and Computer
Engineering Dept. Tucson, AZ, 85721**



Outline

- Introduction
- Background (Previous HF Equalization efforts)
- DFE
- Equalizers Under Test (LMS & CMA)
- Channel Models
- Results
- Conclusions/Next Steps

Introduction



THE UNIVERSITY
OF ARIZONA

High Frequency (3-30 MHz) Band

- Enable long-range communications without significant channel architecture.
- Reflect signals off of ionosphere, no additional equipment required. Enables low-cost communications.
- Lack of equipment also makes High Frequency (HF) systems more reliable in the event of major systematic failure.

Problem Statement

- Ionosphere is unstable medium, constantly fluctuating due to changes in atmospheric conditions:
 - Solar Radiation
 - Seasonal Changes
 - Time of Day
- Ionospheric models, like the Watterson model, have been developed to simulate this behavior but assume that the channel is:
 - Stationary in time and frequency
 - Accurate for small bandwidths
 - Don't capture non-linear effects.

Objective

- Equalizers can be used in the receiver to recover the corrupted signal.
- Adaptive equalization: error between this estimated and transmitted signal is fed into a learning algorithm to adjust the equalizer's coefficients.
- Compare the performance of two adaptive equalizers in the HF channel in linear and non-linear channel models:
 - Least Mean Squares Decision Feedback Equalizer (i.e. LMS-DFE)
 - Constant Modulus Algorithm (CMA) Equalizer

Background



Previous HF Equalization Efforts

- [7] showed that a Decision-Feedback equalizer (DFE) is better suited for the HF channel than maximum-likelihood sequence estimation (MLSE) equalizers.
- Different DFE's implemented over the past few decades:
 - LMS-DFE
 - RLS-DFE
 - Kalman-DFE (using LMS and/or RMS as learning algorithm)
- Blind Equalization
- Turbo Equalization

Decision-Feedback Equalizer (DFE)



DFE Functionality

- Consists of a Feed-Forward and Feedback filter.

$$\hat{\mathbf{I}}_k = \sum_{j=-K_1}^0 c_j \mathbf{v}_{k-j} + \sum_{j=1}^{K_2} c_j \check{\mathbf{I}}_{k-j}$$

Feed-forward filter

Feedback filter

- J and c_j represent the taps of the DFE.
- \mathbf{V} represents the sequences received from the channel.
- $\check{\mathbf{I}}_k$ represents symbols decoded in previous iterations.
- $\hat{\mathbf{I}}_k$ represents the output of the equalizer.

DFE Functionality

- Can use MSE as learning algorithm to adjust the taps.
- Cost Function

$$J(K_1, K_2) = E|I_k - \hat{I}_k|^2$$

- K_1 and K_2 represent the number of taps of the feed-forward and feedback filters.

Least Means Squares and Constant Modulus Algorithms



LMS Algorithm

$$e(n) = d(n) - y(n)$$

$$y(n) = \hat{w}^H(n)u(n)$$

- $e(n)$ represents error
- $d(n)$ represents desired response
- $y(n)$ represents equalized output
- $\hat{w}(n)$ represents estimate of ideal weight vector w .
- H represents Hermitian operator
- $u(n)$ represents input sequence.

LMS Algorithm

- LMS algorithm minimizes following cost function:

$$J(n) = E[|e(n)|^2] \sim e(n)e^*(n)$$

- Update equation given by the following:

$$\hat{w}(n+1) = \hat{w}(n) + \mu u(n)e^*(n)$$

- μ represents step size.
- Knows 'a-prior' information about signal (i.e. modulation).

CMA

- Blind algorithm – has no ‘a-priori’ knowledge of the signal.
- Tries to equalize signals with a constant modulus/amplitude.
- Want to minimize cost function: dispersion
$$D^P = E(|z(n)|^P - R_P)^2$$
- $z(n)$ represents the equalizer output.

CMA

- Steepest descent can be used to minimize dispersion:

$$e_{n+1} = e_n - \mu * \left. \frac{dD^P}{de} \right|_{e=e_n}$$


- e represents the tap of the equalizer
- μ represents the step size
- Assume:
 - $\frac{dD^P}{de} = 0$
 - $z(n) = a(n)e^{j(x+2\pi dfnT)}$
- $R_p = \frac{E[|a(n)|]^{2p}}{E[|a(n)|]^p}$

Channel Models



Watterson Model

- Ionospheric reflections modeled using tapped delay line.
- Each tap has a gain function with bi-variate Gaussian power spectrum.
- Simulates signal being corrupted by Rayleigh fading.



[16]

Watterson Model

- Taps used to generate the main taps of the delay line is accomplished using the following equation:

$$h_n(t) = ke^{-(\pi f_j n T_s)^2}$$

- k is a constant used to preserve unity gain
- f_j represents the Doppler spread.
- n represents the tap index.
- T_s represents the symbol period.

Watterson Model

- Model assumes channel is stationary in time and frequency => accurate for small bandwidths.
- Model was implemented to accept delay spread, Doppler spread and number of taps.
- International Telecommunications Union has defined multiple standards indicative of different HF channel conditions.

Channel Condition	Poor	Moderate
Delay Spread (ms)	2	1
Doppler Spread (Hz)	1	0.5

[18]

Proposed Non-linear Channel Model

- During literature review, have not observed a non-linear ionospheric model as verified/heralded as Watterson's.
- Following equation is our initial attempt to simulate non-linear behavior in the ionosphere:

$$y = x^2 + x + n$$

- y represents signal received by equalizer
- x represents signal corrupted by Watterson model.
- n represents Gaussian noise.

Results



THE UNIVERSITY
OF ARIZONA


System Architecture

- Implemented using GNU Radio and Python.
- 8-PSK used as primary modulation for all experiments.
- Used both Watterson and proposed non-linear models.
- LMS-DD: Knows the constellation (i.e. 8-PSK).
- CMA: Modulus set to 1.
- Parameters for both equalizers:
 - 4 taps
 - Update gain of 0.01
 - 2 Samples/Symbol


MSE Results

- Experiment #1: Observe MSE as SNR is varied.

Mean Squared Error of Equalizers: Poor Channel Conditions




Mean Squared Error of Equalizers: Moderate Channel Conditions




MSE Results

- Experiment #2: Observe MSE as number of samples is varied at a constant SNR.

Mean Squared Error of Equalizers: Poor Channel Conditions




Mean Squared Error of Equalizers: Moderate Channel Conditions




MSE Results

- Repeating Experiment #1 to incorporate non-linear models.

Mean Squared Error of Equalizers: Poor Channel Conditions




Mean Squared Error of Equalizers: Moderate Channel Conditions



MSE Results

- Repeating Experiment #2 to incorporate non-linear models.



Conclusions / Next Steps



Conclusion

- LMS-DD equalizer outperformed CMA algorithm in all experiments.
 - LMS-DD has advantage in knowing constellation prior to equalization.
- Non-linear Ionospheric Model provided higher MSEs than Watterson model.
 - LMS-DD still outperformed CMA under these conditions.
 - Increasing SNR/number of samples is not sufficient for resolving non-linear effects.
- Need additional signal processing to be effective in recovering signals from non-linear effects in the HF channel.

Next Steps

- Incorporate more adaptive equalizers:
 - Minimum Mean Square Equalizer (MMSE)
 - Neural Networks
 - Volterra Equalizers
 - Turbo Equalization
- Refine Non-linear Channel model
- Perform over-the air experiments.

References

- [1] N. Teku, G. Gulati, H. Asadi, G. Vanhoy, A. H. Abdelrahman, K. Morris, T. Bose, and H. Xin, "Design of a long range cognitive hf radio with a tuned compact antenna," International Telemetering Conference 2017, pp. 1–10.
- [2] M. Uysal and M. R. Heidarpour, "Cooperative communication techniques for future-generation hf radios," IEEE Communications Magazine, vol. 50, no. 10, pp. 56–63, October 2012.
- [3] A. D. Sabata and C. Balint, "Structure of signal received by passive ionospheric sounding in the hf band at the location of timisoara, romania," in 2016 12th IEEE International Symposium on Electronics and Telecommunications (ISETC), Oct 2016, pp. 55–58.
- [4] F. H. Raab, R. Caverly, R. Campbell, M. Eron, J. B. Hecht, A. Mediano, D. P. Myer, and J. L. B. Walker, "Hf, vhf, and uhf systems and technology," IEEE Transactions on Microwave Theory and Techniques, vol. 50, no. 3, pp. 888–899, Mar 2002. [5] C. Watterson, J. Juroshek, and W. Bensema, "Experimental confirmation of an hf channel model," IEEE Transactions on Communication Technology, vol. 18, no. 6, pp. 792–803, December 1970.
- [6] Z. Zerdoumi, D. Chikouche, and D. Benatia, "Adaptive decision feedback equalizer based neural network for nonlinear channels," in 3rd International Conference on Systems and Control, Oct 2013, pp. 850–855.
- [7] A. Bartlett, S. M. Brunt, and M. Darnell, "Comparison of DFE and MLSE equalization in a HF serial tone modem and implications for frequency selection," in IEE Colloquium on Frequency Selection and Management Techniques for HF Communications, 1999, pp. 15/1–15/7.

References

- [8] F.A.FaikEken,ErolHepsaydir,“Performance Study ofKalman Adaptive Equalizer for High Speed Data Transmission over the HFChannel,”1988.
- [9] F.Hsu,“Square root Kalman filtering for high-speed data received overfadingdispersiveHFchannels,”IEEETransactionsonInformationTheory,vol.28,no.5,pp.753–763,sep1982.
- [10] E. Eleftheriou and D. Falconer, “Adaptive Equalization Techniques for HF Channels,” IEEE Journal on Selected Areas in Communications,vol.5,no.2,pp.238–247,feb1987.
- [11] R. B. Casey, “Blind Equalization of an Hf Channel For A Passive Listening System,”Ph.D.dissertation,TexasTechUniversity, 2006.
- [12] N. Miroshnikova, “Adaptive Blind Equalizer for HF Channels,” 2017.
- [13] D.Brilyantarto,I.Kurniawati,andG.Hendrantoro,“Early results on the design of adaptive equalizer for HF communications system on equatorial region,”In 2014 XXXIth URSI General Assembly and Scientific Symposium(URSIGASS),aug2014,pp.1–4.
- [14] S. Haykin, Adaptive Filter Theory. Pearson, 2014. [Online]. Available: <https://books.google.com/books?id=J4GRKQEACAAJ>

References

- [15] G.H.Godard, "Self-recovering equalization and carrier tracking in two dimensional data communication systems," IEEE transactions on communications, vol.28, no.11, pp.1867–1875, 1980.
- [16] I.-R. F.1487, "Testing of HF modems with bandwidths of up to about 12 kHz using ionospheric channel simulators," Group, vol. 1487, 2000.
- [17] J.M.Wilson, "A Low Power HF Communication System," Ph.D. dissertation, 2011.
- [18] I. Recommendation, "520-1 Use of high frequency ionospheric channel simulators," Recommendations and Reports of the CCIR, pp.5–8, 1994.
- [19] GNURadio, available at <http://gnuradio.org/>.

Questions???