



Bringing new levels of reliability to deployed Software Defined Radios


Tim Fountain, Director, Business Development

e: tim.fountain@ni.com, p:503-720-2456



Agenda

- Challenges of reliable SDR deployment
- Overview of deployable hardware
- Overview of software features





GNU Radio C++

- Industry leader in SDR
- Broad s/w Development ecosystem
 - C++, GNU Radio, LabVIEW, Mathworks, RedHawk, SCA....
- Vertical Applications Solutions
 - 2G, 3G, 4G, GPS SIM....
- Affordable & flexible H/W
- Deployment + Customization
- Online Support Model



- Highly Productive Software Design Platform
- Extensible Application Focused IP
 - LTE, 802.11, Massive MIMO, mmWave....
- Broad range of H/W from Design to Deployment
- World-class Support & Partner Network
- NI AE Support Model

Challenges of deploying SDR's



- Deployed SDR's present many challenges:
 - The radios can be widely dispersed geographically with no local operator (example – CBRs)
 - Can be difficult, expensive or sometimes impossible to send technicians into the field
 - Failures may be difficult or impossible to diagnose remotely
 - Unit may be functional but operating outside of normal operating parameters (over-temperature for instance) leading to poor MTBF
 - In the worst cases, an SDR may be acquiring or generating erroneous RF data
- Deployed systems often require additional security measures


To date, SDR software has focused solely on data acquisition & generation and data transfer to/from a host system

Requirements for deployed SDR's

- Central management of multiple deployed SDR's
- Separation of processing RF data from management system
- Remote Firmware updates
- Remote OS updates
- Remote reboot
- Remote factory reset
- Remote diagnostics including system health
- Watchdog timer
- Ability to remotely run IQ impairment corrections such as IQ imbalance and DC offset
- Trusted Platform Module (TPM) for secure boot, encryption/decryption & software keying



N310 Overview



USRP N300 Family (NI USRP 2970/2971)



- Channels: up to 4x4 per device
- 100 MHz bandwidth/channel
- 10 MHz – 6 GHz
- Embedded ARM processor for stand-alone operation
- Large user-programmable FPGA
 - Zynq 7100 or Zynq 7035
- 2 x 10 GbE streaming support
- Remote management support
- Rack mountable, half wide, 1U
- Support for Open Source (RFNoC) & LabVIEW Communications

Anticipated Release: Q1 2018 (Open Source), Q4 2018 (LabVIEW)




Applications:

- Communications System Design/Prototyping
 - 802.11, LTE research
 - UE emulation
 - massive MIMO
- SIGINT/EW
- Spectrum Monitoring
- Record & Playback


N300 Family Architecture

ADI 9371 (“Mykonos”)
based daughtercard



Front

ADI 9371- based
daughtercard




ADI 9371 “Mykonos”





N3x0 Motherboard

Rear

N300 Family Motherboard



N300 Family Architecture



Key RF Performance Specifications


- 4 Tx channels, 4 Rx channels
- RF daughtercard based on the new Analog Devices 9371 RFIC
- 16-bit resolution, 100MHz Instantaneous Rx RF bandwidth/channel
- 14-bit resolution, 100 MHz Instantaneous Tx RF bandwidth/channel
- Phase Coherent
- 10MHz – 6GHz Frequency Coverage (possibly down to 2MHz)
- IQ Sampling with IQ imbalance, DC offset calibration
- Programmable 128 tap Tx FIR filter
- Programmable 96 tap Rx FIR filter

ADI 9371 daughterboard



Remote Device Management

- Remote Firmware & OS updates
- Remote reboot
- Remote factory reset
- Remote diagnostics including system health
- Watchdog timer
- Quadrature and DC corrections
- Trusted Platform Module (TPM)



N3x0 Configurations

Feature	Ettus N300/ NI 2970	Ettus N310/NI 2971
Channel Count	2x2	4x4
Rack Mountable	Yes	Yes
FPGA	Zynq-7035 SG2	Zynq-7100 SG2
ARM	800 MHz	800 MHz
SFP+ (1 GigE, 10 GigE)	2 ports	2 ports
RJ45	Yes	Yes
WhiteRabbit (IEEE 1588 & SyncE)	Yes	Yes
Integrated GPS Receiver	Yes	Yes


N310, X310 & E310 FPGA Resources Comparison

	Zynq 7z100 N310	Kintex 7 410T X310	Zynq7z020 E310
Logic Cells	444,000	406,720	85,000
BRAM (MB)	26.5	28.6	4.9
DSP Slices	2,020	1540	220
Flip-flops	554,800	508,400	106,400
LUT's	277,400	254,200	53,200
GMACS	2,622	2,289	276

Ethernet-Based Synchronization

White Rabbit: sub-ns ethernet-based synchronization based on IEEE 1588 and SyncE

- Accuracy: < 1 ns skew, < 100 ps jitter
- Distance: > 10 km
- Scale: $> 2^{32}$




Tools to manage remotely deployed SDR's




- Open Source provides modularity & maintainability
- Over-the-air software updates for embedded Linux devices
- Includes both client and management server, licensed under Apache 2.0
- Designed to work specifically with Yocto images such as the Open Embedded Linux OS used on the N310

Mender Architecture




Building & deploying the Image

- **The software build system** generates a new version of software for a device
- The software build system is a standard component, such as Yocto Project.
- It creates **build artifacts** in the format required by the target device
 - There could be different build artifacts for each type of device being managed
- The build artifacts are passed to the Mender **Management Server**
 - Central point for deploying updates to a population of devices.
 - Server monitors the current software version that is installed on each device and schedules the rollout of new releases.
- **Devices** run the Mender **update client**, which polls the Management Server from time to time to report its status and to discover if there is a software update waiting. If there is, the update client downloads and installs it.




Robust Updates

- Mender employs a dual redundant scheme
 - Each updatable partition is backed up with a duplicate.
 - The one currently in use is the **active partition** a
 - The backup is called the **inactive partition**.
 - Bootloader determines which partition to boot from
- Boot failures set a flag then enables **automatic rollback** to a know-good bootable image
- Images are use a checksum to ensure they are not corrupted
- Cryptography with public and private keys is used to distribute images
- Devices are also authenticated against the server



Installation of new image on a device



- Mender **artifacts** are used to customize deployed images
 - Compatibility flags
 - Checksum
 - Software build name and version
 - Signed image information
 - Optional scripting for both pre and post installation
 - Can be used for data migration, local configuration etc.

Remote Deployment: Mender.IO

- Solution to remote updates of many devices
 - Disclaimer: We will (try) not (to) force tools onto users!

The screenshot displays the Mender.io web interface. At the top, the Mender logo is on the left and a settings gear icon is on the right. Below the logo is a navigation bar with tabs: DASHBOARD, DEVICES (selected), ARTIFACTS, and DEPLOYMENTS. On the left side, under 'Groups', there is a button '+ Create a group' and a summary for 'All devices' showing 40 devices. The main content area is titled '3 devices pending authorization' and contains a table with the following data:

ID	Request time	Status	Authorize?
59aa05d	2017-09-01 18:14	pending	<input checked="" type="checkbox"/> <input type="checkbox"/>
59af218	2017-09-05 15:13	pending	<input checked="" type="checkbox"/> <input type="checkbox"/>
59b07d7	2017-09-06 15:58	pending	<input checked="" type="checkbox"/> <input type="checkbox"/>

Below this table is a pagination control showing '1' of 1 items. To the right of the table is a button labeled 'AUTHORIZE 3 DEVICES'. Below the pending devices section, there is another section titled 'All devices' with a 'FILTERS' button. It contains a table with the following data:

<input type="checkbox"/>	ID	Device type	Current software	Last heartbeat
<input type="checkbox"/>	5983c5d	ni-sulfur-rev3	release-0.10-rc13	2017-09-06 16:36
<input type="checkbox"/>	5983c5e	ni-sulfur-rev3	release-0.10-rc10	2017-09-06 16:43
<input type="checkbox"/>	5983c60	ni-sulfur-rev3	eiscat-image-0.XX	2017-09-06 16:43
<input type="checkbox"/>	5983c7b	ni-sulfur-rev3	release-0.10-rc13	2017-09-06 16:15

Other Management Tools



- Remote reboot
- Remote factory reset
 - Loads known good image
- Remote diagnostics including system health
 - Includes temperature, fan operation etc.
- Watchdog timer
 - Used by local application to keep a heartbeat
- Quadrature and DC corrections to RF front-end
- Trusted Platform Module (TPM)
 - Creates trusted boot and a repository for public & private keys

Thank you

Questions?

