


# Collaborative Spectrum Sensing for Cognitive Radio

**Kamran Arshad & Klaus Moessner**

CCSR, University of Surrey

Guildford, United Kingdom

Email: [k.arshad@surrey.ac.uk](mailto:k.arshad@surrey.ac.uk)





# Outline

---

- Motivation
- Cognitive Radio
- Collaborative Spectrum Sensing
- System Model
- Proposed weighted framework for collaborative spectrum sensing
- Results and discussions
- Conclusion




# Main Contributions

## Problem

How to fuse local observations of cognitive radios at fusion centre to decide globally the existence of licensed user?



## Solution Approach

For a given channel conditions and targeted probability of false alarm, weights are assigned to the secondary user observations in such a way that it maximises global probability of detection. Optimum weights are calculated using genetic algorithm



# Motivation

- Spectrum Scarcity Problem
  - Limited resource, overcrowded, future technologies need more spectrum
- Spectrum Underutilisation Problem
  - Studies by Ofcom and FCC show that at some locations 70% of the spectrum sitting idle




*Technologu Research Programme: Research and Development at Ofcom 2004/05, issued: 24 October 2005, p.37*



# Cognitive Radio

“Cognitive radio is a paradigm for wireless communication in which either a network or a mobile node changes its transmission or reception parameters to communicate efficiently in licensed or unlicensed band by avoiding interference with licensed users”






# Why Cognitive Radio?

- Because Cognitive Radio:
  - significantly increase spectrum efficiency
  - optimise use of under utilised spectrum without (or with minimum) interference to the primary users
  - can access the large, normally hidden, spectral resource called, WHITE SPACE:

WHITE SPACE






# Spectrum Sensing

We are here!

- Goal is to reliably detect the presence of Primary (Licensed) User
- Three main approaches:
  - Match Filter detection
  - Energy Detection
  - Cyclostationary Feature Detection

We use this!


- Optimal detector
- Simple architecture
- Easy to implement
- Less complexity





# Collaborative Spectrum Sensing

- Local spectrum sensing limitations
  - Hidden node problem
  - Performance loss in fading and shadowing
- Solution
  - Collaborative or Cooperative Spectrum Sensing
- Collaborative Spectrum Sensing
  - Mechanism in which a number of cognitive radios share their sensing information with each other
  - Nodes send information to the fusion centre which combines local decision and make a global decision








# System Model

Primary User



Scenario 1




Primary  
Receiver



Cognitive  
Radio with  
sensing  
capabilities

Primary User



Scenario 2



# Problem definition

- Maximise global probability of detection at the fusion centre, considering
  - Two scenarios (users with same mean SNR and with different mean SNR values)
  - Noisy reporting channels with channel gains
- Global probability of detection can be defined as  $Q_d = Q(f(w))$ , where  $f(w)$  is given by


$$f(w) = \frac{\sqrt{\text{Var}[y_c/\mathcal{H}_0]} Q^{-1}(Q_f) + E[y_c/\mathcal{H}_0] - E[y_c/\mathcal{H}_1]}{\sqrt{\text{Var}[y_c/\mathcal{H}_1]}}$$

$$= \frac{Q^{-1}(Q_f) \sqrt{w^T A w} - w^T [\text{diag}(g) \text{diag}(\sigma)]}{\sqrt{w^T B w}}$$

where matrices **A** and **B** are defined as,


$$A = 2N \text{diag}^2(g) \text{diag}^2(\sigma) + \text{diag}(\delta)$$

$$B = 2(N I_M + 2 \text{diag}(\bar{\gamma})) \text{diag}^2(g) \text{diag}^2(\sigma) + \text{diag}(\sigma)$$




minimise  $f(w)$

st.  $\|w\|_2^2 = 1$  and  $w_i > 0 \forall i \in \{1, 2, 3, \dots, M\}$






# Proposed weighted framework





# Why genetic algorithms?


- Very useful for complex and loosely defined problems.
- Quickly can scan a vast solution set.
- Global optimisation technique.
- Does not have to know any rules of the problem.
  - It works by its own internal rules.
- Supports parallel processing.
  - Multiple solution capability





# Results and Discussions (1/4)

ROC curves for single CR, SNR = 5B




Performance loss due  
To fading



# Results and Discussions (2/4)

Effect of different SNR values (perfect reporting channels)




Performance loss due  
different SNR values



## Results and Discussions (3/4)

### Performance of proposed scheme with 6 users and imperfect reporting channel

Rayleigh Channel



Performance by algorithm



# Conclusion

---

- Collaborative spectrum sensing improves sensing performance significantly
- Different SNR of users have significant effect on the performance of collaborative spectrum sensing
- Proposed Genetic Algorithm based weighted collaborative spectrum sensing improves sensing performance in all cases
- Proposed scheme requires knowledge about SNR of each user as well as channel conditions
  - Larger reporting channel bandwidths are required
  - Topic of our future research





# Acknowledgment

---



This work was performed in project E3 which has received research funding from the Community's Seventh Framework programme. This paper reflects only the author's views and Community is not liable for any use that may be made of the information contained therein. The contributions of colleagues from E3 consortium are hereby acknowledged.



# Questions ????

---

