



HARRIS[®] DSA WITHIN MILITARY NETWORKING WAVEFORMS

NICK VAN STRALEN

THIS INFORMATION IS NOT EXPORT CONTROLLED

THIS INFORMATION IS APPROVED FOR PUBLISHING PER THE ITAR AS "FUNDAMENTAL RESEARCH" AND THE EAR AS "EDUCATIONAL INFORMATION"

RF Communications

March 11 2014 - 1

Dynamic Spectral Allocation is a Cognitive Radio Technology whereby a radio or a network of radios sense their operating environment and adapt their spectral usage in response to the sensed environment.

Radios Should




- Transmit only on allowed frequencies
- Cease transmitting when using secondary frequency when interference detected by self or when informed by others
- Co-operate with other cognitive radios in use of primary and secondary frequencies

DSA Promise



DSA radios must ...

- adaptively utilize the spectrum to improve performance, flexibility, and deployment time
- coordinate and select their own frequencies
- adapt to changes in the RF environment and sustain reliable network communication connections
- improve network performance



Ad-Hoc Networks

- Proactively maintain membership, establish routes, monitor call groups
- Other DSA enabled networks sharing the same set of primary and/or secondary frequencies
- Non DSA radios enabled networks
- Sharing of UHF, VHF and L-band frequencies

Military Networks – Primary or Secondary ?

- Primary – always available for use to the network
- Secondary – available on non-interfering basis

Reliance on external information (when it exists)

- Broadcast Environmental database
- Timing from GPS signals

Frequency or spectrum that has had interference in the past

No frequency recovery

- Intermittent interferences 'chases' radios away from available operating frequencies

Policies

- How long and what signal level
- Do all nodes in network need to agree
- Do rules changes when running out of frequencies

Approach - Single Frequency



Advantage – quick to rendezvous but ...

Exclusion

- Group moves frequency due to local interference
- Interference prevents signaling to other radios
- Some terminals may be excluded

Abandonment

- Group is operating on a single frequency
- Interference is detected – must go to another frequency
- Policy states – interference is detected, radio must not transmit

Impairment of interference assessment

- In a busy network, time is dedicated to transmitting information
- Can easily miss intermittent sources.

Frequency Agile networks possible solve some of the fixed frequency problems but introduce new ones

Rendezvous

- Potentially a lot of frequencies that network or group is using. Rendezvous is a difficult problem.
- Rendezvous time is $O(N)$ where N is the number of possible operating frequencies

Hopping pattern synchronization

- When we have received first message in a hopping system, we can gain time sync,
- Frequency pattern is chosen dynamically, so remainder of pattern needs to be determined.

Harris DSA is a slow, synchronous-hop-based blind-rendezvous approach

- Networked radios coordinate & select their own frequencies
- They dynamically adapt to changes in RF environment
- High-sensitivity multiple-waveform sensing detects signals below noise floor
- Epoch synchronized to GPS time supports fast late-net-entry & group merge
- Also support non-GPS time synchronization
- Better bandwidth utilization means more radios without performance drop
- Can use TV whitespace, unlicensed spectrum, & share assigned frequencies
- Can use secondary frequencies when primary frequencies are degraded

Information Sharing



Quick Dissemination

- Notification of NEW occupied frequency
- Just 14 bits each beacon period

Slow



- Full occupied state information

Coordinated messaging

- All nodes in the network act at the same time
 - Frequency Recovery

Detect

Multiple-waveform sensor detects signals below noise
In signal band



Adapt

Adaptive frequency agility (Hopping) maintains links during interference mitigation actions




FIG. 10

Harris DSA networks ...

- Detect wideband and narrow band signals
- Automatically coordinate frequency agility set across network
- Maintain user traffic flows during frequency changes

Demonstrated with ANW2 waveform on AN-PRC 117G

- Real time sensing and adaptation with live streaming video

Opportunistic Sensing

- Waveform informs sensor when it does not need use of RF interface
- Sensor schedules and executes sensing
 - Multiple senses if there is enough time
- Front end use restored to waveform for next transmission or reception event
- Remaining time in receive window when preamble detect is not triggered

Policy/Configuration

- Specification of what frequencies are available to radio set
- Primary / Secondary
- Spectral Use policy
- Database interfaces

Frequency selection

- Frequency selection algorithms

Sensor Control

- Competes with radio for front-end control
- DSA competes with other RF sensing applications

Sensing Core

- Collects statistics from RF environment

