

DISIMAN: A Distributed Simulator for MANet in Software Defined Radio technology

Authors

M. Colizza F. Santucci M. Faccio

University of L'Aquila

Center of Excellence DEWS



Summary

- Introduction
 - Mobile Ad-hoc Networks
 - SDR Technology
 - SCA
- Open issues in the Software Communication Architecture (SCA)
 - Reconfigurability and Scalability
 - Routing and QoS
- A modelling approach to overcome limitations of the SCA
 - The Use Case of the IEEE 802.15.4 Physical Layer
- Tissue Methodology (TM): A network modelling approach for design, simulation and emulation of a SDR MANET device
- DISIMAN
- Conclusion and future works
- Publications



Introduction



Mobile Ad-hoc Networks

- MANET are ad-hoc networks where each device works both as a terminal and as a router, without the support of an infrastructure communication network
- Some present and future applications concerning the MANET
 - Tactical Networks



Mobile Ad-hoc Networks

- Some present and future applications concerning the MANET
 - Tactical Networks
 - Military Communication and operations



Mobile Ad-hoc Networks

- Some present and future applications concerning the MANET
 - Tactical Networks
 - Military Communication and operations
 - ESSOR



Mobile Ad-hoc Networks

- Some present and future applications concerning the MANET
 - Tactical Networks
 - Military Communication and operations
 - ESSOR
 - Emergency Service



Mobile Ad-hoc Networks

- Some present and future applications concerning the MANET
 - Tactical Networks
 - Military Communication and operations
 - ESSOR
 - Emergency Service
 - Replacement of fixed infrastructure in case of environmental disaster



Mobile Ad-hoc Networks

- Some present and future applications concerning the MANET
 - Tactical Networks
 - Military Communication and operations
 - ESSOR
 - Emergency Service
 - Replacement of fixed infrastructure in case of environmental disaster
 - Commercial and Civilian environments



Mobile Ad-hoc Networks

- Some present and future applications concerning the MANET
 - Tactical Networks
 - Military Communication and operations
 - ESSOR
 - Emergency Service
 - Replacement of fixed infrastructure in case of environmental disaster
 - Commercial and Civilian environments
 - Vehicular services: road or accident guidance, transmission of road and weather conditions, taxi cab network, inter-vehicle networks



Mobile Ad-hoc Networks

- Some present and future applications concerning the MANET
 - Tactical Networks
 - Military Communication and operations
 - ESSOR
 - Emergency Service
 - Replacement of fixed infrastructure in case of environmental disaster
 - Commercial and Civilian environments
 - Vehicular services: road or accident guidance, transmission of road and weather conditions, taxi cab network, inter-vehicle networks
 - Home and enterprise networking



Mobile Ad-hoc Networks

- Some present and future applications concerning the MANET
 - Tactical Networks
 - Military Communication and operations
 - ESSOR
 - Emergency Service
 - Replacement of fixed infrastructure in case of environmental disaster
 - Commercial and Civilian environments
 - Vehicular services: road or accident guidance, transmission of road and weather conditions, taxi cab network, inter-vehicle networks
 - Home and enterprise networking
 - Home/office wireless networking



Mobile Ad-hoc Networks

- Some present and future applications concerning the MANET
 - Tactical Networks
 - Military Communication and operations
 - ESSOR
 - Emergency Service
 - Replacement of fixed infrastructure in case of environmental disaster
 - Commercial and Civilian environments
 - Vehicular services: road or accident guidance, transmission of road and weather conditions, taxi cab network, inter-vehicle networks
 - Home and enterprise networking
 - Home/office wireless networking
 - Sensor networks



Mobile Ad-hoc Networks

- Some present and future applications concerning the MANET
 - Tactical Networks
 - Military Communication and operations
 - ESSOR
 - Emergency Service
 - Replacement of fixed infrastructure in case of environmental disaster
 - Commercial and Civilian environments
 - Vehicular services: road or accident guidance, transmission of road and weather conditions, taxi cab network, inter-vehicle networks
 - Home and enterprise networking
 - Home/office wireless networking
 - Sensor networks
 - Body area networks (BAN)



Mobile Ad-hoc Networks

- Some present and future applications concerning the MANET
 - Networked Control Systems
 - HYCON 2: This project aims at stimulating and establishing a long-term integration in the strategic field of control of complex, large-scale, and networked dynamical systems



SDR Technology



SDR Technology

- The Software Defined Radio, (SDR) is a technology useful to realize devices for MANET. This is because a SDR devices has the following features:
 - The ability to generate a base-band waveform, for different radio bands and different protocols, by a set of algorithms implemented by a programming language on programmable architecture for digital signals processing;
 - The ability to execute signal recognition operations, in order to identify available communication services inside an environment;



SCA



SCA

- SCA is based on several underlying technologies: Object-Orientation (OO) design, the Common Object Request Broker Architecture (CORBA), and CORBA Component Model (CCM)



SCA

- SCA is based on several underlying technologies: Object-Orientation (OO) design, the Common Object Request Broker Architecture (CORBA), and CORBA Component Model (CCM)
- CORBA is an industry standard for describing interfaces using Interface Description Language (IDL)



SCA

- SCA is based on several underlying technologies: Object-Orientation (OO) design, the Common Object Request Broker Architecture (CORBA), and CORBA Component Model (CCM)
- CORBA is an industry standard for describing interfaces using Interface Description Language (IDL)
- IDL allows designers to specify the interfaces between two components, then an IDL compiler generates the code necessary to support communication between the components – using remote procedure calls (RPC)



SCA

- SCA is based on several underlying technologies: Object-Orientation (OO) design, the Common Object Request Broker Architecture (CORBA), and CORBA Component Model (CCM)
- CORBA is an industry standard for describing interfaces using Interface Description Language (IDL)
- IDL allows designers to specify the interfaces between two components, then an IDL compiler generates the code necessary to support communication between the components – using remote procedure calls (RPC)
- RPC on the client contacts RPC on the server (e.g., by opening a network connection), and sends over the function parameters



SCA

- SCA is based on several underlying technologies: Object-Orientation (OO) design, the Common Object Request Broker Architecture (CORBA), and CORBA Component Model (CCM)
- CORBA is an industry standard for describing interfaces using Interface Description Language (IDL)
- IDL allows designers to specify the interfaces between two components, then an IDL compiler generates the code necessary to support communication between the components – using remote procedure calls (RPC)
- RPC on the client contacts RPC on the server (e.g., by opening a network connection), and sends over the function parameters
- RPC on the server executes the function with the received parameters and returns the result



Open issue in the Software Communication Architecture (SCA)

- The remote procedure calls can be between processes on the same computer or between computers, i.e. in a distributed environment



Open issue in the Software Communication Architecture (SCA)

- The remote procedure calls can be between processes on the same computer or between computers, i.e. in a distributed environment
- The issue concerning the exchange of message between routines executed on different processors was first addressed in the context of supercomputers, and standard message passing techniques were developed (e.g., message passing interface (MPI)) for high performance and lowlevel programming. MPI deals exclusively with data exchange



Open issue in the Software Communication Architecture (SCA)

- The remote procedure calls can be between processes on the same computer or between computers, i.e. in a distributed environment
- The issue concerning the exchange of message between routines executed on different processors was first addressed in the context of supercomputers, and standard message passing techniques were developed (e.g., message passing interface (MPI)) for high performance and lowlevel programming. MPI deals exclusively with data exchange
- CORBA is one of the most specific characteristics of the SCA




Open issue in the Software Communication Architecture (SCA)

- The remote procedure calls can be between processes on the same computer or between computers, i.e. in a distributed environment
- The issue concerning the exchange of message between routines executed on different processors was first addressed in the context of supercomputers, and standard message passing techniques were developed (e.g., message passing interface (MPI)) for high performance and lowlevel programming. MPI deals exclusively with data exchange
- CORBA is one of the most specific characteristics of the SCA
- Every CORBA server object has a unique object reference. In order to invoke the methods implemented by this server, a client needs to know this reference.



Reconfigurability and Scalability



Routing and QoS



Routing and QoS

- Cross-layer design is an emerging proposal to support flexible layer approaches in MANETs



Routing and QoS

- Cross-layer design is an emerging proposal to support flexible layer approaches in MANETs
- The development of MAC and dynamic routing protocols is a central challenge in the design of ad hoc networks



Routing and QoS

- Cross-layer design is an emerging proposal to support flexible layer approaches in MANETs
- The development of MAC and dynamic routing protocols is a central challenge in the design of ad hoc networks
- This is because the issue is to find routes with QoS assurance between communicating nodes



Routing and QoS

- Cross-layer design is an emerging proposal to support flexible layer approaches in MANETs
- The development of MAC and dynamic routing protocols is a central challenge in the design of ad hoc networks
- This is because the issue is to find routes with QoS assurance between communicating nodes
- The high mobility degree of the nodes causes changes in the topology. These changes may be fast and unpredictably



Routing and QoS

- Cross-layer design is an emerging proposal to support flexible layer approaches in MANETs
- The development of MAC and dynamic routing protocols is a central challenge in the design of ad hoc networks
- This is because the issue is to find routes with QoS assurance between communicating nodes
- The high mobility degree of the nodes causes changes in the topology. These changes may be fast and unpredictably
- Physical layer, MAC layer and routing layer together contend for the network resources




Routing and QoS


- In [CPSP12] we propose a cross-layer design among physical, MAC and routing layers.



Routing and QoS



- Number of hosts: 25
- Mobility model: random way-point mobility
- Area: 50 [m] × 50 [m]
- Transmission power: 2 [mW]
- Path-loss factor: 3
- Signal to noise ratio: -110 [dBm]
- Simulation time: 600 [s]





	ETX	PER
Unacked bytes	3760	585
Transmission time	72 [s]	402 [s]
Average congestion window	48473	10905




A modelling approach to overcome the limits of the SCA





The Use Case of the IEEE 802.15.4 Physical Layer




The Use Case of the IEEE 802.15.4 Physical Layer



The Use Case of the IEEE 802.15.4 Physical Layer



The Use Case of the IEEE 802.15.4 Physical Layer



- Architecture proposed in:
 - at *Wireless Innovation Forum European Conference on Communications Technologies* ([CFR12])
 - *Wireless Telecommunications Symposium* ([CFRS12])





Simulation and emulation issue: a solution by using the Tissue Methodology






Figure 13: Network Storage.



Simulation and emulation issue: a solution by using the Tissue Methodology




Simulation and emulation issue: a solution by using the Tissue Methodology




Simulation and emulation issue: a solution by using the Tissue Methodology

EMUTools – 1st Workshop on Emulation Tools, Methodology and Techniques
([CNPR13])




DISIMAN



Conclusion

What's?



Scalability

Distributed File System	A Distributed File System allows to split a file of big size in more files small. These small files may be stored on many remote hosts[Ref.2].
Distributed Computing	Distributed Computing is a field of computer science that studies distributed systems. A distributed system is a software system in which components located on networked computers communicate and coordinate their actions by passing messages[Ref.1].



Conclusion

How?




DISIMAN

Distributed File System	HBASE
Distributed Computing	AKKA




DISIMAN

HBASE




DISIMAN


AKKA ➡ Actor Model
[Ref.3]



DISIMAN



DISIMAN



Future Works

Study of a Tissue Architecture for
Software Defined Networks







Study of a Tissue Architecture for Software Defined Networks

- The Open Networking Foundation (ONF) says:
 - *“In the Software Defined Networks (SDN), the control and data planes are decoupled, network intelligence and state are logically centralized, and the underlying network infrastructure is abstracted from the applications”*
- SDN focuses on four key features:
 - Separation of the control plane from the data plane;
 - A centralized controller and view of the network;
 - Open interfaces between the devices in the control plane (controllers) and those in the data plane
- The architecture requirements to meet operational expectations in carrier grade networks are:
 - scalability
 - reliability,
 - quality of service (QoS),
 - service management



Study of a Tissue Architecture for Software Defined Networks



Publications

- **[CFR12]** M. Colizza, M. Faccio, C. Rinaldi, **A component-based architecture for protocol design and development in SDR frameworks**, *Wireless Innovation Forum European Conference on Communications Technologies*, 27-29 June 2012, Brussels, Belgium
- **[CFRS12]** M. Colizza, M. Faccio, C. Rinaldi, F. Santucci, **A methodology to design an advanced framework for efficient modelling and testing of MANETs**, *Wireless Telecommunications Symposium (WTS)*, 2012
- **[CPSP12]** M. Colizza, M. Pratesi, F. Santucci, S. Pollio, G. Rigazzi, **Performance of OLSR in MANETs with Cross-Layer Metrics and TCP/UDP flows**, *WIRELESS COMMUNICATIONS, NETWORKING AND MOBILE COMPUTING*, September 21-23, 2012, Shanghai, China
- **[CRS12]** M. Colizza, C. Rinaldi, I. J. Senese, **A Generalized Waveform Identifier Technique for Software Radio**, *INTERNATIONAL SYMPOSIUM ON COMMUNICATIONS, CONTROL AND SIGNAL PROCESSING*, May 2-4, 2012, Rome, Italy
- **[CFRS13]** M. Colizza, M. Faccio, C. Rinaldi, F. Santucci, **A Methodology for Design of Scalable Architectures in Software Radio Networks: a Unified Device and Network Perspective**, *J Sign Process Syst* (2013) 73:315-323
- **[CNPR13]** M. Colizza, L. De Nardis, M. Patrizi, C. Rinaldi, **A novel architecture for a framework to support the storage of network simulation data into distributed storages for remote access**, *EMUTools – 1st Workshop on Emulation Tools, Methodology and Techniques*, Cannes, French Riviera March 5-7, 2013



Others References

1. Coulouris, George; Jean Dollimore; Tim Kindberg; Gordon Blair (2011). Distributed Systems: Concepts and Design (5th Edition). Boston: Addison-Wesley. ISBN 0-132-14301-1
2. Silberschatz, Galvin (1994). Operating System concepts, chapter 17 Distributed file systems. Addison-Wesley Publishing Company. ISBN 0-201-59292-4.
3. Carl Hewitt; Peter Bishop; Richard Steiger (1973). A Universal Modular Actor Formalism for Artificial Intelligence. IJCAI.




Questions?



Backup




A network oriented approach to design, simulation and emulation of Wireless Embedded Systems




A network oriented approach to design, simulation and emulation of Wireless Embedded Systems






Why?




A network oriented approach to design, simulation and emulation of Wireless Embedded Systems



A network oriented approach to design, simulation and emulation of Wireless Embedded Systems



Conclusion and future works




AKKA


HAZELCAST

JBOSS + EJB + JSF



Conclusion and future works





Conclusion

- The objectives of this research activity may be summarized as follows:
 - Identification of a cross-layer approach to improve the throughput of TCP and UDP protocols, inside MANET networks ([CFRS13]
 - Identification of an architectural solution able to overcome the scalability and re-configurability issues of the SCA architecture, useful to develop SDR devices for MANET applications ([CFR12], [CFRS12], [CPSP12]);
 - Identification of a methodology useful to develop wireless embedded systems; the proposed methodology is named: "Tissue Methodology";
 - The development of simulation/emulation environment for wireless embedded systems ([CPSP12] , [CRS12]), using the Tissue Methodology.

