

ESC Sensor Nodes Placement and Location for Moving Incumbent Protection in CBRS

Satya Joshi, Shashika Manosha, Markku Jokinen, Tuomo Hänninen, Pekka Pirinen, Harri Posti, and Matti Latva-aho

{sjoshi, manosha, markku.jokinen, tuomo.hanninen, pekka.pirinen, harri.posti, matti.latva-aho}@ee.oulu.fi

Centre for Wireless Communications, University of Oulu, Finland

Introduction

- ❑ **Citizens Broadband Radio Service (CBRS):** share the spectrum between federal incumbent and commercial users
- ❑ Incumbents: ship borne radar, group based radar, fixed satellite service earth station, wireless broadband services
- ❑ key to **success of Spectrum Access System (SAS)** – protection of incumbent users from the harmful interference generated by CBSDs
 - protection via exclusion zone
 - protection via a use of environmental sensing capability (ESC) network
 - ESC network converts the exclusion zone into a protection zone

Introduction

- ❑ **Citizens Broadband Radio Service (CBRS):** share the spectrum between federal incumbent and commercial users
- ❑ Incumbents: ship borne radar, group based radar, fixed satellite service earth station, wireless broadband services
- ❑ key to **success of Spectrum Access System (SAS)** – protection of incumbent users from the harmful interference generated by CBSDs
 - protection via exclusion zone
 - protection via a use of environmental sensing capability (ESC) network
 - ESC network converts the exclusion zone into a protection zone

Introduction

- ❑ **Citizens Broadband Radio Service (CBRS):** share the spectrum between federal incumbent and commercial users
- ❑ Incumbents: ship borne radar, group based radar, fixed satellite service earth station, wireless broadband services
- ❑ key to **success of Spectrum Access System (SAS)** – protection of incumbent users from the harmful interference generated by CBSDs
 - protection via exclusion zone
 - protection via a use of environmental sensing capability (**ESC**) network
 - ESC network converts the exclusion zone into a protection zone

Introduction

❑ Challenges in the deployment of ESC network

- moving incumbents
- detecting the location of the federal naval incumbent is forbidden
- optimum number of sensors and their locations

Introduction

- ❑ Challenges in the deployment of ESC network
 - moving incumbents
 - detecting the location of the federal naval incumbent is forbidden
 - optimum number of sensors and their locations

Introduction

- ❑ Challenges in the deployment of ESC network
 - moving incumbents
 - detecting the location of the federal naval incumbent is forbidden
 - optimum number of sensors and their locations

Our Work

- ❑ ESC sensor placement problem in coastal areas for the moving incumbent protection in CBRS
 - protection – by deploying minimum number of sensors
 - robustness against sensor failure


Our Work

- ❑ ESC sensor placement problem in coastal areas for the moving incumbent protection in CBRS
 - protection – by deploying minimum number of sensors
 - robustness against sensor failure


Our Work

- ❑ ESC sensor placement problem in coastal areas for the moving incumbent protection in CBRS
 - protection – by deploying minimum number of sensors
 - robustness against sensor failure


System Model




System Model




System Model



System Model




System Model



x_s : ESC sensor place

d_i : isolation knot point

System Model



x_s : ESC sensor place

d_i : isolation knot point

S : number of sensor places


\mathcal{S} : set of sensor places

D : number of isolation
knot points

\mathcal{D} : set of isolation knot points

R : radius sensing region

System Model



x_s : ESC sensor place

d_i : isolation knot point

S : number of sensor places

\mathcal{S} : set of sensor places


D : number of isolation knot points

\mathcal{D} : set of isolation knot points

R : radius sensing region

\mathcal{S}_i : subset of \mathcal{S}


System Model



Euclidean distance from d_i to x_s

$$\text{dist}(d_i, x_s) = \|d_i - x_s\|_2$$

System Model



Euclidean distance from d_i to x_s


$$\text{dist}(d_i, x_s) = \|d_i - x_s\|_2$$

nearest sensor place for d_i

$$r_i^{\min} = \inf_{s \in \mathcal{S}} \text{dist}(d_i, x_s)$$

$$= \inf_{s \in \mathcal{S}_i} \text{dist}(d_i, x_s)$$

System Model




a sensor position that can detect incumbent at d_i

$$r_i^{\min} \leq \sum_{s \in \mathcal{S}_i} b_{is} \|d_i - x_s\|_2 \leq R$$

$$\sum_{s \in \mathcal{S}_i} b_{is} = 1$$

$$b_{is} = \{0, 1\}, \quad s \in \mathcal{S}_i$$


System Model



place sensor at \mathcal{X}_S :

$$a_s = \begin{cases} 1 & \text{if } b_{is} = 1 \text{ for any } i \in \mathcal{D} \\ 0 & \text{otherwise} \end{cases}$$

System Model



place sensor at \mathcal{X}_S :

$$a_s = \begin{cases} 1 & \text{if } b_{is} = 1 \text{ for any } i \in \mathcal{D} \\ 0 & \text{otherwise} \end{cases}$$

let, $\mathbf{a} = [a_1, \dots, a_S]^T$

required sensors, $\text{card}(\mathbf{a})$

Minimum number of ESC sensors

$$\begin{aligned}
 &\text{minimize} && \mathbf{card}(\mathbf{a}) \\
 &\text{subject to} && r_i^{\min} \leq \sum_{s \in \mathcal{S}_i} b_{is} \|d_i - x_s\|_2 \leq R, \quad i \in \mathcal{D} \\
 & && \sum_{s \in \mathcal{S}_i} b_{is} = 1, \quad i \in \mathcal{D} \\
 & && b_{is} = \{0, 1\}, \quad i \in \mathcal{D}, s \in \mathcal{S} \\
 & && \max\{b_{1s}, \dots, b_{Ds}\} = a_s, \quad s \in \mathcal{S},
 \end{aligned}$$

variables: $\{a_s\}_{s \in \mathcal{S}}$ and $\{b_{is}\}_{i \in \mathcal{D}, s \in \mathcal{S}}$

Minimum number of ESC sensors

$$\begin{aligned} &\text{minimize} && \text{card}(\mathbf{a}) \\ &\text{subject to} && r_i^{\min} \leq \sum_{s \in \mathcal{S}_i} b_{is} \|d_i - x_s\|_2 \leq R, \quad i \in \mathcal{D} \\ & && \sum_{s \in \mathcal{S}_i} b_{is} = 1, \quad i \in \mathcal{D} \\ & && b_{is} = \{0, 1\}, \quad i \in \mathcal{D}, s \in \mathcal{S} \\ & && \max\{b_{1s}, \dots, b_{Ds}\} = a_s, \quad s \in \mathcal{S}, \end{aligned}$$

variables: $\{a_s\}_{s \in \mathcal{S}}$ and $\{b_{is}\}_{i \in \mathcal{D}, s \in \mathcal{S}}$

- ❑ combinatorial optimization problem
- ❑ exponential complexity – global solution

Minimum number of ESC sensors

$$\begin{aligned}
 &\text{minimize} && \text{card}(\mathbf{a}) \\
 &\text{subject to} && r_i^{\min} \leq \sum_{s \in \mathcal{S}_i} b_{is} \|d_i - x_s\|_2 \leq R, \quad i \in \mathcal{D} \\
 & && \sum_{s \in \mathcal{S}_i} b_{is} = 1, \quad i \in \mathcal{D} \\
 & && b_{is} = \{0, 1\}, \quad i \in \mathcal{D}, s \in \mathcal{S} \\
 & && \max\{b_{1s}, \dots, b_{Ds}\} = a_s, \quad s \in \mathcal{S},
 \end{aligned}$$

variables: $\{a_s\}_{s \in \mathcal{S}}$ and $\{b_{is}\}_{i \in \mathcal{D}, s \in \mathcal{S}}$


- ❑ combinatorial optimization problem
- ❑ exponential complexity – global solution
- ❑ propose: suboptimal but fast algorithm
(sequential convex programming)

Robustness against sensor failures (N-measurements)

$$\begin{aligned}
 &\text{minimize} && \text{card}(\mathbf{a}) \\
 &\text{subject to} && r_i^{\min} \leq \sum_{s \in \mathcal{S}_i} b_{is} \|d_i - x_s\|_2 \leq NR, \quad i \in \mathcal{D} \\
 &&& \sum_{s \in \mathcal{S}_i} b_{is} = N, \quad i \in \mathcal{D} \\
 &&& b_{is} \in \{0, 1\}, \quad i \in \mathcal{D}, s \in \mathcal{S} \\
 &&& \max\{b_{1s}, \dots, b_{Ds}\} = a_s, \quad s \in \mathcal{S},
 \end{aligned}$$

variables: $\{a_s\}_{s \in \mathcal{S}}$ and $\{b_{is}\}_{i \in \mathcal{D}, s \in \mathcal{S}}$

Numerical Results




possible sensor positions

$$S = 140$$

$$D = 20$$

Numerical Results




possible sensor positions

$$S = 140$$


$$D = 20$$

$R = 2.5$ and 5 [distance unit]

Numerical Results




convergence of algorithm




required sensors vs iterations

Numerical Results




$R = 2.5$ [distance unit]

Numerical Results



$R = 5$ [distance unit]

Numerical Results




$R = 5$ [distance unit]

$N = 2$

$\delta = 1$

Numerical Results



$R = 5$ [distance unit]

$N = 2$

$\delta = 5$

Conclusions

- ❑ sensor node placement in the coastal areas for the moving incumbent protection is considered
- ❑ problem of finding the minimum number of ESC sensors and their locations is a combinatorial optimization problem
- ❑ proposed a suboptimal but fast-converging algorithm based on sequential convex programming
- ❑ extend the proposed algorithm to overcome the sensor failures